

-1-

ELECTRONIC LOCATION MONITORING SYSTEM**CROSS REFERENCE TO RELATED APPLICATION**

This application claims priority from United States Provisional Application No. 60/497,017 filed on August 22, 2003.

BACKGROUND OF THE INVENTION**1. Field of Invention**

This invention relates to remote monitoring and more particularly to remote monitoring in an electronic location monitoring system.

2. Description of Related Art

As an alternative to incarcerating offenders for minor infractions, more and more judicial and law enforcement agencies prefer to place such offenders under house arrest and monitor their movement using electronic location monitoring equipment. As a result, there is less space taken in already overcrowded detention facilities such as prisons, thus eliminating the cost of incarceration, while at the same time allowing offenders to avoid prison and provide them with the opportunity to attend school or earn a wage and participate in counseling or rehabilitation programs.

Electronic location monitoring equipment usually involves the use of an identification tag securely attached to the individual's body, which periodically transmits a unique code to an RF receiver device placed in the incarcerated individual's place of confinement (usually his or her house). The receiver listens for transmissions from the identification tag, and if a transmission is not received within a predetermined amount of time, an event is logged by the receiver indicating that the identification tag, and hence the individual wearing it, is no longer in the vicinity of the receiver. In turn, the receiver transmits a status message to a monitoring station over a communication channel such

as the PSTN (Public Switched Telephone Network) indicating the presence or absence of the individual at the monitored site.

5 The electronic location monitoring approach described above works well to ensure that the individual remains in the monitored area according to the conditions of his/her parole. However, once the individual is away from the monitored site and out of range of the receiver, the individual cannot be reached. Law enforcement agencies usually want to ensure that the individual is at particular locations (not just one monitored site) at particular times. For
10 example the individual may be required to be at work during certain hours, at a counseling workshop during other hours, and at home at all other times. In some cases, it is also necessary to ensure that the individual stays away from certain locations (for e.g., schools, parks, home of an ex-spouse, etc.).

15 To overcome this problem, systems are known in which an incarcerated individual wears a transmitter and carries a receiver operable to receive signals from the transmitter. The receiver may perform calculations based on position signals it may receive to determine whether the individual is in an allowable location and may permit the individual to venture outside of a single
20 area. One problem with this type of system however is that the individual must carry the receiver with him/her at all times, which can be somewhat inconvenient. For example when the receiver is being charged, the individual must stay relatively near the charger. Consequently, this type of system can be restrictive.

25 SUMMARY OF THE INVENTION

In accordance with one aspect of the invention, there is provided a method for operating a monitoring unit operable to receive signals from a mobile transmitter in an electronic location monitoring system. The method involves
30 causing a receiver of the monitoring unit to change a signal reception threshold thereof for receiving signals from the mobile transmitter, in response to proximity of the monitoring unit relative to a reference position whereby the

-3-

receiver rejects signals received from the mobile transmitter that have a signal strength below the signal reception threshold and receives and processes signals received from the mobile transmitter that have a signal strength above the signal reception threshold.

5

Changing the signal reception threshold may involve causing the receiver to decrease the signal reception threshold when the monitoring unit is in proximity to the reference position and causing the receiver to increase the signal reception threshold when the monitoring unit is not in proximity to the reference position.

10

The method may involve detecting proximity of the monitoring unit relative to the reference position.

15

The method may involve producing a proximity signal for reception by the receiver, in response to detecting the change in proximity of the monitoring unit relative to the reference position, whereby the receiver changes the signal reception threshold in response to the proximity signal.

20

The method may involve causing the proximity signal to indicate the monitoring unit is in proximity to the reference position when the monitoring unit is coupled to a docking station.

25

The method may involve causing the proximity signal to indicate the monitoring unit is not in proximity to the reference position when the monitoring unit is uncoupled from a docking station.

30

The method may involve receiving position signals at the monitoring unit, the position signals representing a geographical position of the monitoring unit, and producing the proximity signal in response to the position signals.

-4-

The method may involve causing the proximity signal to indicate the monitoring unit is in proximity to the reference position when the position signals meet a first position criterion.

- 5 The first position criterion may be met when the position signals indicate the monitoring unit is within a first range of the reference position.

10 The method may involve causing the proximity signal to indicate the monitoring unit is not in proximity to the reference position when the position signals meet a second position criterion.

The second position criterion may be met when the position signals indicate the monitoring unit is within a second range of the reference position.

15 In accordance with another aspect of the invention, there is provided an apparatus operable to receive signals from a mobile transmitter in an electronic location monitoring system. The apparatus includes a proximity signal generator operable to generate a proximity signal in response to proximity of the apparatus relative to a reference position, a receiver operable
20 to receive signals from the mobile transmitter, the receiver having a signal reception threshold responsive to the proximity signal, such that the receiver rejects signals from the mobile transmitter that have a signal strength below the signal reception threshold and receives signals from the mobile transmitter that have a signal strength above the signal reception threshold and a
25 processor circuit operable to process signals received by the receiver to produce processed signals, the processor circuit being operable to communicate with a transmitter to cause the transmitter to transmit the processed signals to a monitoring station.

30 The receiver may be operable to decrease the signal reception threshold when the proximity signal indicates the apparatus is in proximity to the reference position and the receiver may be operable to increase the signal

reception threshold when the proximity signal indicates apparatus is not in proximity to the reference position.

5 The proximity signal generator may comprise a detector operable to detect proximity of the apparatus to the reference position.

10 The detector may be operable to detect coupling of the apparatus to a docking station, and to cause the proximity signal to indicate the apparatus is in proximity to the reference position when the apparatus is coupled to the docking station.

15 The detector may be operable to detect uncoupling of the receiver from the docking station and to cause the proximity signal to indicate the apparatus is not in proximity to the reference position when the apparatus is uncoupled from the docking station.

20 The detector may comprise a position signal receiver operable to receive position signals representing a geographical position of the apparatus, the proximity signal generator being operable to produce the proximity signal in response to the position signals.

25 The detector may be operable to cause the proximity signal to indicate the apparatus is in proximity to the reference position when the position signals meet a first position criterion.

The detector may be configured to determine the first position criterion is met when the position signals indicate the apparatus is within a first range of the reference position.

30 The detector may be operable to cause the proximity signal to indicate the apparatus is not in proximity to the reference position when the position signals meet a second position criterion.

-6-

The detector may be configured to determine the second position criterion is met when the position signals indicate the apparatus is within a second range of the reference position.

5

The position signal receiver may comprise a global positioning system (GPS) signal receiver.

10

The position signal receiver may include a wireless receiver operable to receive position signals from a wireless communication network.

The position signal receiver may comprise a message receiver operable to receive messages from a messaging system.

15

The message receiver may be operable to receive a message compatible with the SMS message format or the GPRS/CDMA 1X, CDPD, Mobitex, or 1XRTT data packet format, or any other suitable format.

20

The apparatus may be incorporated into a modular battery unit.

The apparatus may further include a first mobile wireless transceiver powered by the modular battery unit and in communication with the apparatus such that the wireless transceiver is operable to transmit the processed signals to the monitoring station.

25

The processor circuit may be configured to implement a portion of the proximity signal generator.

30

The processor circuit may be configured to cause the processed signals to include a representation of the proximity signal.

-7-

In accordance with another aspect of the invention, there is provided an apparatus operable to receive signals from a mobile transmitter in an electronic location monitoring system. The apparatus includes provisions for generating a proximity signal in response to proximity of the apparatus relative to a reference position, provisions for receiving signals from the mobile transmitter, the provisions for receiving having a signal reception threshold responsive to the proximity signal, such that signals from the mobile transmitter that have a signal strength below the signal reception threshold are rejected and such that signals from the mobile transmitter that have a signal strength above the signal reception threshold are received and provisions for processing signals received by the receiver to produce processed signals, the provisions for processing being operable to communicate with a transmitter to cause the transmitter to transmit the processed signals to a monitoring station.

The provisions for receiving may be operable to decrease the signal reception threshold when the proximity signal indicates the apparatus is in proximity to the reference position and operable to increase the signal reception threshold when the proximity signal indicates apparatus is not in proximity to the reference position.

In accordance with another aspect of the invention, there is provided a method for switching monitoring units in an electronic location monitoring system comprising a mobile transmitter operable to transmit to at least one of first and second monitoring units operable to communicate with a common monitoring station. The method involves detecting proximity of the first monitoring unit relative to the second monitoring unit, producing a proximity signal in response to detecting proximity of the first monitoring unit relative to the second monitoring unit, for reception by the first monitoring unit to cause the first monitoring unit to enter a receive mode in which processing of signals received from the mobile transmitter by the first monitoring unit is permitted when the first monitoring unit is not in proximity to the second monitoring unit

-8-

or a low power mode in which processing of signals received from the mobile transmitter by the first monitoring unit is prevented when the first monitoring unit is in proximity to the second monitoring unit and causing the second monitoring unit to receive and process signals from the mobile transmitter when the proximity signal indicates the first monitoring unit is in proximity to the second monitoring unit and causing the second monitoring unit to cease receiving signals from the mobile transmitter when the proximity signal indicates the first monitoring unit is not in proximity to the second monitoring unit.

The method may involve causing the proximity signal to indicate the first monitoring unit is in proximity to the second monitoring unit when the first monitoring unit is coupled to a docking station associated with the second monitoring unit.

The method may involve causing the proximity signal to indicate the first monitoring unit is not in proximity to the second monitoring unit when the first monitoring unit is uncoupled from a docking station associated with the second monitoring unit.

Detecting may involve measuring, near the second monitoring unit, signal strength of signals received from the mobile transmitter, and wherein the proximity signal is produced in response to measured signal strength.

The method may involve causing the proximity signal to indicate the first monitoring unit is in proximity to the second monitoring unit when measured signal strength meets a first signal strength criterion.

The first signal strength criterion may be met when the measured signal strength is above a first signal strength threshold value.

-9-

The method may involve causing the proximity signal to indicate the first monitoring unit is not in proximity to the second monitoring unit when measured signal strength meets a second signal strength criterion.

- 5 The second signal strength criterion may be met when the measured signal strength is below a second signal strength threshold value.

The first and second signal strength threshold values may be the same.

- 10 Detecting may comprise receiving position signals at the first monitoring unit, the position signals representing a geographical position of the first monitoring unit, and producing the proximity signal in response to the position signals.

- 15 The method may involve causing the proximity signal to indicate the first monitoring unit is in proximity to the second monitoring unit when the position signals meet a first position criterion.

- 20 The first position criterion may be met when the position signals indicate the first monitoring unit is within a first range of a reference position.

- 25 The method may involve causing the proximity signal to indicate the first monitoring unit is not in proximity to the second monitoring unit when the position signals meet a second position criterion.

- 30 The second position criterion may be met when the position signals indicate the first monitoring unit is within a second range of the reference position.

The reference position may represent an approximate geographical position of the second monitoring unit.

- 35 Producing the proximity signal may comprise causing a message to be transmitted to the first monitoring unit.

-10-

The method may involve causing a message to be transmitted to the first monitoring unit through a messaging service.

5 Causing a message to be transmitted to the first monitoring unit through a messaging service may involve causing a message compatible with the SMS message format or the GPRS/CDMA 1X, CDPD, Mobitex, or 1XRTT data packet format, or any other suitable format to be transmitted to the first monitoring unit.

10 The message may include a power down command when the first monitoring unit is in proximity to the second monitoring unit and the message may include a power up command when the first monitoring unit is not in proximity to the second monitoring unit.

15 In accordance with another aspect of the invention, there is provided an apparatus for switching monitoring units in an electronic location monitoring system comprising a mobile transmitter operable to transmit to at least one of first and second monitoring units operable to process signals received from
20 the mobile transmitter and transmit processed signals to a monitoring station. The apparatus includes a detector operable to produce a proximity signal indicating proximity of the first monitoring unit relative to the second monitoring unit and a first transmitter operable to cause the proximity signal to be communicated to the first monitoring unit such that, when the proximity
25 signal indicates the first monitoring unit is in proximity to the second monitoring unit the first monitoring unit enters a low power mode in which signals are not received from the mobile transmitter by the first monitoring unit and when the proximity signal indicates that the first monitoring unit is not in proximity to the second monitoring unit the first monitoring unit enters a
30 receive mode in which signals from the mobile transmitter are received and processed by the first monitoring unit. The apparatus further includes a second transmitter operable to cause the proximity signal to be transmitted to

-11-

the second monitoring unit such that in response to the proximity signal the second monitoring unit receives and processes signals from the mobile transmitter when the proximity signal indicates the first monitoring unit is in proximity to the second monitoring unit and ceases receiving signals from the mobile transmitter when the proximity signal indicates the first monitoring unit is not in proximity to the second monitoring unit.

The detector may be operable to cause the proximity signal to indicate the first monitoring unit is in proximity to the second monitoring unit when the first monitoring unit is coupled to a docking station.

The detector may be operable to cause the proximity signal to indicate the first monitoring unit is not in proximity to the second monitoring unit when the first monitoring unit is uncoupled from a docking station.

The detector may comprise a signal strength detector operable to detect signal strength of signals received from the mobile transmitter, and the detector may produce the proximity signal in response to measured signal strength.

The detector may cause the proximity signal to indicate the first monitoring unit is in proximity to the second monitoring unit when measured signal strength meets a first signal strength criterion.

The detector may determine the first signal strength criterion is met when the measured signal strength is above a first signal strength threshold value.

The detector may cause the proximity signal to indicate the first monitoring unit is not in proximity to the second monitoring unit when measured signal strength meets a second signal strength criterion.

-12-

The detector may determine the second signal strength criterion is met when the measured signal strength is below a second signal strength threshold value.

5 The first and second signal strength threshold values may be the same.

10 The detector may include a position signal receiver operable to receive position signals representing a geographical position of the first monitoring unit, and the detector may produce the proximity signal in response to the position signals.

15 The detector may cause the proximity signal to indicate the first monitoring unit is in proximity to the second monitoring unit when the position signals meet a first position criterion.

20 The detector may determine the first position criterion is met when the position signals indicate the first monitoring unit is within a first range of a reference position.

25 The detector may cause the proximity signal to indicate the first monitoring unit is not in proximity to the second monitoring unit when the position signals meet a second position criterion.

30 The detector may determine the second position criterion is met when the position signals indicate the first monitoring unit is within a second range of the reference position.

35 The reference position may represent an approximate geographical position of the second monitoring unit.

40 The first transmitter may be operable to transmit a message representing the proximity signal to the first monitoring unit.

-13-

The apparatus may further include a first messaging service interface operable to transmit a message to the first monitoring unit through a messaging service.

5

The first messaging service interface may be operable to transmit a message compatible with the SMS message format or the GPRS/CDMA 1X, CDPD, Mobitex, or 1XRTT data packet format, or any other suitable format to be transmitted to the first monitoring unit.

10

The second transmitter may be operable to transmit a message representing the proximity signal to the second monitoring unit.

15

The apparatus may further include a second messaging service interface operable to transmit a message to the second monitoring unit through a messaging service.

20

The second messaging service interface may be operable to transmit a message compatible with the SMS message format or the GPRS/CDMA 1X, CDPD, Mobitex, or 1XRTT data packet format, or any other suitable format to be transmitted to the second monitoring unit.

25

The apparatus may further include a modular battery unit, operable to power the first monitoring unit. The detector, the first transmitter and the second transmitter may be incorporated into the modular battery unit.

30

The apparatus may further include a housing and the detector, the first transmitter, the second transmitter and the second monitoring unit may be housed in the housing.

The housing may have a docking station to facilitate docking of the first monitoring unit.

-14-

In accordance with another aspect of the invention, there is provided an apparatus for use in an electronic location monitoring system. The apparatus includes a first monitoring unit comprising a first receiver operable to receive signals from a mobile transmitter on a person to be monitored, the first receiver having a low power mode in which signals are not received from the mobile transmitter and a receive mode in which signals from the mobile transmitter are received. The first monitoring unit further includes a processor circuit for processing signals received by the first receiver to produce processed signals and a transmitter operable to transmit the processed signals to a monitoring station. The apparatus further includes a signaling unit comprising a detector operable to produce a proximity signal indicating proximity of the first monitoring unit relative to a second monitoring unit operable to receive, process and transmit signals to the monitoring station, the first receiver being responsive to the proximity signal such that, when the proximity signal indicates the first monitoring unit is in proximity to the second monitoring unit the first receiver is placed in the low power mode and when the proximity signal indicates that the first monitoring unit is not in proximity to the second monitoring unit the first receiver enters the receive mode. The signaling unit further includes a proximity signal transmitter operable to cause the proximity signal to be transmitted to the second monitoring unit, whereby in response to the proximity signal the second monitoring unit receives and processes signals from the mobile transmitter when the proximity signal indicates the first monitoring unit is in proximity to the second monitoring unit and ceases receiving signals from the mobile transmitter when the proximity signal indicates the first monitoring unit is not in proximity to the second monitoring unit. The first monitoring unit receives and processes signals from the mobile transmitter and the second monitoring unit does not receive and process signals from the mobile transmitter when the first monitoring unit is not in proximity to the second monitoring unit and the second monitoring unit receives and processes signals from the mobile transmitter and the first monitoring unit does not receive and process signals from the mobile

-15-

transmitter when the first monitoring unit is in proximity to the second monitoring unit.

5 The apparatus may further include a modular battery unit operable to power the first monitoring unit and the signaling unit and wherein the first monitoring unit and the signaling unit may be housed in the modular battery unit.

10 The apparatus may further include a portable wireless communication appliance. The apparatus may be incorporated into the portable wireless communication appliance.

The portable wireless communication appliance may include a cellular telephone.

15 The detector may be operable to cause the proximity signal to indicate the first monitoring unit is in proximity to the second monitoring unit when the first monitoring unit is coupled to a docking station.

20 The detector may be operable to cause the proximity signal to indicate the first monitoring unit is not in proximity to the second monitoring unit when the first monitoring unit is uncoupled from a docking station.

25 The detector may comprise a signal strength detector operable to detect signal strength of signals received from the mobile transmitter, and the detector may produce the proximity signal in response to measured signal strength.

30 The detector may cause the proximity signal to indicate the first monitoring unit is in proximity to the second monitoring unit when measured signal strength meets a first signal strength criterion.

-16-

The detector may determine the first signal strength criterion is met when the measured signal strength is above a first signal strength threshold value.

5 The detector may cause the proximity signal to indicate the first monitoring unit is not in proximity to the second monitoring unit when measured signal strength meets a second signal strength criterion.

10 The detector may determine the second signal strength criterion is met when the measured signal strength is below a second signal strength threshold value.

The first and second signal strength threshold values may be the same.

15 The detector may comprise a position signal receiver operable to receive position signals representing a geographical position of the first monitoring unit and the detector may produce the proximity signal in response to the position signals.

20 The detector may cause the proximity signal to indicate the first monitoring unit is in proximity to the second monitoring unit when the position signals meet a first position criterion.

25 The detector may determine the first position criterion is met when the position signals indicate the first monitoring unit is within a first range of a reference position.

30 The detector may cause the proximity signal to indicate the first monitoring unit is not in proximity to the second monitoring unit when the position signals meet a second position criterion.

-17-

The detector may determine the second position criterion is met when the position signals indicate the first monitoring unit is within a second range of the reference position.

- 5 The reference position may represent an approximate geographical position of the second monitoring unit.

The proximity signal transmitter may be operable to transmit a message representing the proximity signal to the second monitoring unit.

10

The apparatus may further include a messaging service interface operable to transmit a message to the second monitoring unit through a messaging service.

- 15 The messaging service interface may be operable to transmit a message compatible with the SMS message format or the GPRS/CDMA 1X, CDPD, Mobitex, or 1XRTT data packet format, or any other suitable format to be transmitted to the second monitoring unit.

- 20 In accordance with another aspect of the invention, there is provided a docking apparatus for a first monitoring unit in an electronic location monitoring system in which the first monitoring unit has a first receiver operable to receive signals from a mobile transmitter on a person to be monitored and wherein the first monitoring unit is operable to process the
- 25 signals to produce processed signals and to transmit the processed signals to a monitoring station. The docking apparatus comprises a second monitoring unit comprising a second receiver operable to receive signals from the mobile transmitter, the second receiver having a non-receive mode in which signals are not received from the mobile transmitter and a receive mode in which
- 30 signals from the mobile transmitter are received. The second monitoring unit includes a processor circuit for processing signals received by the second receiver to produce processed signals and a transmitter operable to transmit

-18-

the processed signals to the monitoring station. The docking apparatus further includes a signaling unit comprising a detector operable to produce a proximity signal indicating proximity of the first monitoring unit relative to the second monitoring unit, the second receiver being responsive to the proximity signal such that, when the proximity signal indicates the first monitoring unit is in proximity to the second monitoring unit the second receiver is placed in the receive mode and when the proximity signal indicates that the first monitoring unit is not in proximity to the second receiver unit is placed in the non-receive mode. The signaling unit further includes a proximity signal transmitter operable to cause the proximity signal to be transmitted to the first monitoring unit, whereby in response to the proximity signal the first monitoring unit receives and processes signals from the mobile transmitter when the proximity signal indicates the first monitoring unit is not in proximity to the second monitoring unit and ceases receiving signals from the mobile transmitter when the proximity signal indicates the first monitoring unit is in proximity to the second monitoring unit. The first monitoring unit receives and processes signals from the mobile transmitter and the second monitoring unit does not receive and process signals from the mobile transmitter when the first monitoring unit is not in proximity to the second monitoring unit and the second monitoring unit receives and processes signals from the mobile transmitter and the first monitoring unit does not receive and process signals from the mobile transmitter when the first monitoring unit is in proximity to the second monitoring unit.

The docking station apparatus may include a docking port to which the first monitoring unit may be coupled.

The detector may be operable to cause the proximity signal to indicate the first monitoring unit is in proximity to the second monitoring unit when the first monitoring unit is coupled to the docking station.

-19-

The detector may be operable to cause the proximity signal to indicate the first monitoring unit is not in proximity to the second monitoring unit when the first monitoring unit is uncoupled from the docking station.

5 The detector may comprise a signal strength detector operable to detect signal strength of signals received from the mobile transmitter and the detector may produce the proximity signal in response to measured signal strength.

10 The detector may cause the proximity signal to indicate the first monitoring unit is in proximity to the second monitoring unit when measured signal strength meets a first signal strength criterion.

15 The detector may determine the first signal strength criterion is met when the measured signal strength is above a first signal strength threshold value.

20 The detector may cause the proximity signal to indicate the first monitoring unit is not in proximity to the second monitoring unit when measured signal strength meets a second signal strength criterion.

The detector may determine the second signal strength criterion is met when the measured signal strength is below a second signal strength threshold value.

25 The first and second signal strength threshold values may be the same.

30 The detector may comprise a position signal receiver operable to receive position signals representing a geographical position of the first monitoring unit and the detector may produce the proximity signal in response to the position signals.

-20-

The detector may cause the proximity signal to indicate the first monitoring unit is in proximity to the second monitoring unit when the position signals meet a first position criterion.

5 The detector may determine the first position criterion is met when the position signals indicate the first monitoring unit is within a first range of a reference position.

10 The detector may cause the proximity signal to indicate the first monitoring unit is not in proximity to the second monitoring unit when the position signals meet a second position criterion.

15 The detector may determine the second position criterion is met when the position signals indicate the first monitoring unit is within a second range of the reference position.

The reference position may represent an approximate geographical position of the second monitoring unit.

20 The first transmitter may be operable to transmit a message representing the proximity signal to the first monitoring unit.

The apparatus may further include a messaging service interface operable to transmit a message to the first monitoring unit through a messaging service.

25 The messaging service interface may be operable to transmit a message compatible with the SMS message format or the GPRS/CDMA 1X, CDPD, Mobitex, or 1XRTT data packet format, or any other suitable format to be transmitted to the first monitoring unit.

30 Other aspects and features of the present invention will become apparent to those ordinarily skilled in the art upon review of the following description of

-21-

specific embodiments of the invention in conjunction with the accompanying figures.

BRIEF DESCRIPTION OF THE DRAWINGS

5 In drawings which illustrate embodiments of the invention,

Figure 1 is a schematic diagram of an electronic location monitoring system according to a first embodiment of the invention,

10 Figure 2 is a block diagram of a wireless communication appliance according to a first embodiment of the invention;

Figure 3 is a schematic diagram of an electronic location monitoring system according to a second embodiment of the invention,

15 Figure 4 is a block diagram of a signaling apparatus shown in Figure 3;

Figure 5 is a block diagram of a mobile communication appliance incorporating a monitoring unit and the signaling apparatus of
20 Figure 4;

Figure 6 is a block diagram of a stationary communication appliance incorporating a monitoring unit and the signaling apparatus of
25 Figure 4;

DETAILED DESCRIPTION

Referring to Figure 1, an electronic location monitoring system according to a first embodiment of the invention is shown generally at 10. The system includes a mobile transmitter 12 which may be strapped onto an incarcerated
30 person by non-removable bands, a strap, or other permanent securing means. The mobile transmitter may incorporate tamper detection mechanisms that, where a strap is used, may detect severing of a strap, or a change in the

-22-

resistance of a strap circuit, caused by attempting to electrically jumper it. The mobile transmitter may be housed in a waterproof casing and may also include tamper detection circuitry, which may include detection of case tampering or proximity to skin, for example.

5

The mobile transmitter **12** periodically transmits a beacon signal **14** encoded with information that may include a transmitter identification code, battery status code, tamper status code and/or other information. The beacon signal **14** may be transmitted periodically at a frequency of about **433** MHz, for example, but any radio frequency may be used. Furthermore, the mobile transmitter **12** may communicate with the receiver on multiple communication channels, so that if one channel experiences interference, the other communication channel may still be functional. The mobile transmitter **12** need only transmit the beacon signal **14** at a power level sufficient to permit the signal to be detected a short distance away. A power level sufficient to permit the beacon signal **14** to be detected about **300** feet away is sufficient.

10

15

20

In the embodiment shown, the system **10** further includes a wireless communication appliance **16**, which may include a wireless telephone, for example. Referring to Figure 2, the wireless communication appliance **16** includes a first transceiver **18** operable to receive from and transmit signals to a base station **20** shown in Figure 1 of a public communications network such as a cellular telephone network, for communication to a monitoring station **22** via the same network or the public switched telephone network.

25

30

Referring back to Figure 2, in the embodiment shown, the wireless communication appliance **16** is powered by a removable modular battery unit **24** having a bus interface **26** that allows it to communicate with a processor circuit **28** of the wireless communication appliance. According to an aspect of the invention, a monitoring unit apparatus **30** operable to receive signals from the mobile transmitter **12** shown in Figure 1 is included within the modular battery unit **24** and is operable to communicate with the processor circuit **28** of

-23-

the wireless communication appliance **16** through the bus interface **26**. Alternatively, the apparatus **30** may be incorporated as a functional block of the wireless communication appliance **16**, for example.

5 In the embodiment shown, the apparatus **30** includes a proximity signal generator **32** operable to generate a proximity signal in response to proximity of the monitoring unit apparatus **30** relative to a reference position, a receiver **34** operable to receive signals from the mobile transmitter (**12**), and a processor circuit **36** operable to process signals received by the receiver to
10 produce processed signals for communication to the monitoring station. The processor circuit **36** is operable to communicate with the first transceiver **18** of the wireless communication appliance **16** through the bus interface **26** and the processor circuit **28** of the wireless communication appliance to cause the first transceiver **18** to transmit the processed signals to the monitoring station **22**
15 shown in Figure 1.

Of particular importance to the monitoring unit apparatus **30** is the receiver **34** as it is specially configured to have a signal reception threshold responsive to the proximity signal, such that the receiver rejects signals from the mobile
20 transmitter (**12**) that have a signal strength below the signal reception threshold and receives signals from the mobile transmitter that have a signal strength above the signal reception threshold. In general, the receiver **34** is operable to decrease the signal reception threshold (i.e., increase sensitivity) when the proximity signal indicates the monitoring unit apparatus **30** is in
25 proximity to the reference position and to increase the signal reception threshold (i.e., decrease sensitivity) when the proximity signal indicates monitoring unit apparatus **30** is not in proximity to the reference position.

The proximity signal generator **32** includes a detector **38** operable to detect
30 proximity of the monitoring unit apparatus **30** to the reference position. Various types of detectors may be employed for this purpose. For example, in one embodiment the detector **38** is operable to detect coupling of the

-24-

wireless communication appliance **16** to a docking station **40** such as shown in Figure 1, and to cause the proximity signal to indicate the monitoring unit apparatus **30** is in proximity to the reference position when the wireless communication appliance **16** is coupled to the docking station. The position of the docking station is thus the reference position. Similarly, the detector **38** is operable to detect uncoupling of the wireless communication appliance from the docking station **40** and to cause the proximity signal to indicate the monitoring unit apparatus **30** is not in proximity to the reference position when the wireless communication appliance **16** is uncoupled from the docking station.

Coupling to the docking station **40** may involve receiving the wireless communication appliance **16** in a receptacle of the docking station, plugging the wireless communication appliance into a pigtail connector of the docking station, or engaging a wireless link such as a Bluetooth® link, or infrared link between the docking station and the mobile wireless communication appliance, for example.

A detector operable to detect coupling and uncoupling may be implemented by causing the processor circuit **36** in the apparatus to communicate through the bus interface **26** with the processor circuit **28** of the wireless communication appliance **16** to receive a signal indicating that the communication appliance has been docked in a docking station compatible with the communication appliance. The processor circuit **28** in the wireless communication appliance may detect whether the wireless communication appliance **16** is placed in the docking station. A modification may be made to a program controlling the processor circuit **28** in the wireless communication appliance **16** to cause it to set a flag at a port accessible through the bus interface **26** and readable by the processor circuit **36** of the apparatus **30**, depending upon whether the wireless communication appliance **16** is or is not in the docking station (**40**). The flag itself may act as the proximity signal, in which case the processor circuit **28** of the wireless communication appliance

-25-

16 may be considered to act as at least a portion of the proximity signal generator **32**.

Alternatively, especially where the docking station **40** is configured to charge the battery unit when the communication appliance is in the docking station **40**, the detector **38** may be configured to monitor signals applied to a battery **42** thereof and detect the direction of current flow relative to the battery whereby the proximity signal is set active to indicate proximity of the monitoring unit apparatus **30** to the reference position when the current flow is into the battery and is set inactive to indicate the wireless communication appliance is out of proximity with the reference position, when the current flow is out of the battery. In this embodiment, the reference position corresponds to the position of the docking station (**40**).

In another embodiment, the detector **38** may include a position signal receiver **44** operable to receive position signals representing a geographical position of the wireless communication appliance **16** and hence the monitoring unit apparatus **30** and the proximity signal generator **32** produces the proximity signal in response to the position signals. The position signal receiver **44** may be of a type that comprises a global positioning system (GPS) signal receiver **46**, or a Long Range Radio Navigation (LORAN) receiver **48**, for example. The position signals produced by the position signal receiver may include all or a subset of the following data items, for example: latitude, longitude, altitude, horizontal velocity, vertical velocity, heading, and a measure of precision of the location fix. The position information may be time-stamped and data logged along with the mobile transmitter **12** status data in a data log. The date and time used to time-stamp the data may be obtained from the GPS receiver or the wireless telecommunication network, or even possibly via messages from the central monitoring center computer that the wireless communication appliance reports to. These messages may include a message compatible with the SMS message format or the GPRS/CDMA 1X,

-26-

CDPD, Mobitex, or 1XRTT data packet format, or any other suitable format, for example.

5 Alternatively, the position signal receiver may include the processor circuit **36** of the apparatus **30**, which may communicate with the processor circuit **28** of the wireless communication appliance **16** to cause the first receiver to receive position signals provided by the wireless communication network. Such signals may be produced by the wireless communication network in response to triangulation techniques involving a plurality base stations (**20**) in communication with the wireless communication appliance **16**, for example, as is known in the art. In such an embodiment, the position signal receiver **44** may be considered to include the first transceiver **18** of the wireless communication appliance. In one embodiment, the position signal receiver **44** may include a message receiver **50** operable to receive messages from a messaging system, the messages including data representing position signals specifying the geographical position of the monitoring unit apparatus **30**. Effectively, the position signal produced by the wireless network by triangulation, may be formatted in a message compatible with the SMS message format or the GPRS/CDMA 1X, CDPD, Mobitex, or 1XRTT data packet format, or any other suitable format, for example, and sent to the wireless communication appliance, where position information may be extracted from the messages by the processor circuit **28** of the wireless communication appliance or the processor circuit **36** of the apparatus **30**.

25 In embodiments employing the position signal receiver **44**, regardless of how the position signals are received at the apparatus, the detector **38** is operable to cause the proximity signal to indicate the monitoring unit apparatus **30** is in proximity to the reference position when the position signals meet a first position criterion. The detector **38** may be implemented by the processor circuit **28** of the wireless communication appliance **16** or by the processor circuit **36** of the apparatus **30**, or by parts of these circuits or by both. The

30

-27-

detector **38** may be configured to determine the first position criterion is met when the position signals indicate the monitoring unit apparatus **30** is within a first range of the reference position. For example, the detector **38** may be configured to cause the proximity signal to indicate the monitoring unit apparatus **30** is in proximity to the reference position when the position signals indicate the first receiver is within **300** feet (**100m**) of the reference position. The reference position may correspond to the geographical position of the home, school or workplace of the incarcerated individual, for example.

Similarly, the detector **38** may be operable to cause the proximity signal to indicate the monitoring unit apparatus **30** is not in proximity to the reference position when the position signals meet a second position criterion and the detector may be configured to determine the second position criterion is met when the position signals indicate the monitoring unit apparatus **30** is within a second range of the reference position. For example, the detector **38** may be configured to cause the proximity signal to indicate the monitoring unit apparatus **30** is not in proximity to the reference position when the position signals indicate the apparatus is more than **300** feet (**100m**) from the reference position.

When the monitoring unit apparatus **30** is not in proximity to the reference position, as indicated by the proximity signal, in response to the proximity signal, the receiver **34** maintains the receive threshold at a relatively high value. The receive threshold can be held at a relatively high value because it is expected that the incarcerated individual will carry the wireless communication appliance with him/her while away from his/her home or workplace, where the docking station **40** may be kept, for example. Since the incarcerated individual wears the mobile transmitter **12** and the wireless communication appliance **16** is carried by the incarcerated individual when away from the docking station **40**, the mobile transmitter and the receiver **34** of the apparatus **30** are relatively close to each other and thus, the receiver need not be ultra sensitive to the beacon signal.

-28-

When the monitoring unit apparatus **30** is in proximity to the reference position, as indicated by the proximity signal, in response to the proximity signal, the receiver **34** decreases its receive threshold to a relatively low value. If the reference position is the geographical location of the docking station, for example, the receive threshold is decreased when the wireless communication appliance is in the docking station **40** in the home, school or workplace. The decrease in receive threshold permits the incarcerated individual wearing the mobile transmitter **12** to move freely within a radius of the docking station **40** without having to carry the wireless communication appliance **16**. The wireless communication appliance **16** is thus less obtrusive.

Regardless of the level of the receive threshold, beacon signals having a signal strength above the receive threshold are received and processed by the processor circuit **36** to extract the information pertaining to the identification, tamper status and battery level. Such processing may involve time-stamping a received beacon signal and storing it for producing signals for transmission to the monitoring station **22** through the first transceiver **18** of the wireless communication appliance **16**. In addition, a representation of the proximity signal may be included in the signals transmitted to the monitoring station **22**. The signals transmitted to the monitoring station **22** may include signals representing a message such as a message compatible with the SMS message format or the GPRS/CDMA 1X, CDPD, Mobitex, or 1XRTT data packet format, or any other suitable format, for example. The monitoring station is thus informed of the status of the mobile transmitter **12**.

When the monitoring unit apparatus **30** is not in proximity to the reference position, the receiver **34** may listen for transmissions from the mobile transmitter **12** having a signal strength associated with a range of about 10-20 feet. When the monitoring unit apparatus **30** is in proximity to the reference position, the receiver **34** may listen for transmissions from the mobile

-29-

transmitter **12** having a signal strength associated with a range of about **300** feet.

5 Regardless of the range, if the receiver **34** does not receive any transmission from the mobile transmitter **12** within a specified duration, it may assume that the mobile transmitter **12** (and hence the individual wearing the transmitter device) is not at the location of the wireless handset. The processing by the processor circuit **36** may involve keeping track of the current status, i.e., whether the apparatus **30** is within the specified range of the mobile
10 transmitter **12** in an internal data log.

The position information as well as status information regarding the mobile transmitter **12** identification may be transmitted to the monitoring station **22** using the wireless telecommunications network. The position information and
15 status information may be transmitted continuously at specified intervals, or alternatively, the processor circuit **36** may periodically store the position information in internal data memory, and periodically send all location stored points at one time to the monitoring station **22**.

20 Similarly, it may also be possible for the monitoring station **22** to use messaging to query the apparatus **30** for its current location as well as the status of its matched mobile transmitter **12**. An authorized user may also make such a query by messaging with a suitable wireless communication device from any place that allows wireless communication to be established.
25 In addition to querying the current location and status from the wireless handset device, position and mobile transmitter status data logged in the internal memory of the apparatus may be selectively downloaded by messaging.

30 The monitoring station may also send messages to the apparatus to cause it to alter its receiver sensitivity, set criteria for determining position conditions, configure the receiver **34** for use with different mobile transmitters **12**,

-30-

configure time intervals for transmissions to the monitoring station, download alarm events, receive alert or warning messages for annunciation to the incarcerated individual, and perform other functions as may be required. Such messages may include a message compatible with the SMS message format or the GPRS/CDMA 1X, CDPD, Mobitex, or 1XRTT data packet format, or any other suitable format, for example.

It will be appreciated that the apparatus 30 may include a receiver 34 operable to receive different beacon signals from a plurality of different mobile transmitters 12, on a plurality of different channels and that the channels may be scanned, for example for active beacon signals. Each signal received on each channel may be provided to the processor circuit 36 by multiplexing, for example to consider each signal separately. This allows a single wireless communication appliance to be used to simultaneously monitor a plurality of incarcerated individuals.

Referring to Figure 3, a signaling apparatus facilitating switching of monitoring units in an electronic location monitoring system 100 comprising a mobile transmitter 112 operable to transmit to at least one of first and second monitoring units 114 and 116 operable to communicate with a monitoring station 118 is shown generally at 101.

The first monitoring unit 114 includes a first receiver 113 (or transceiver) operable to receive signals from the mobile transmitter 112. The first receiver 113 has a low power mode in which signals are not received from the mobile transmitter 112 and a receive mode in which signals are received from the mobile transmitter. The first monitoring unit 114 further includes a processor circuit 115 for processing signals received by the first receiver 113 to produce processed signals and includes a transmitter 117 (or transceiver) operable to transmit processed signals to the monitoring station 118. The first monitoring unit may be included within a wireless communication appliance 130, for example.

-31-

The second monitoring unit **116** includes a second receiver **119** (or transceiver) operable to receive signals from the mobile transmitter **112**. The second receiver **119** has a non-receive mode in which signals are not received from the mobile transmitter **112** and a receive mode in which signals are received from the mobile transmitter **112**. The second monitoring unit **116** further includes a processor circuit **121** for processing signals received by the second receiver **119** to produce processed signals and includes a transmitter **123** operable to transmit processed signals to the monitoring station **118**.

The first and second monitoring units **114** and **116** may both be mobile, but it is contemplated that the first monitoring unit **114** will be part of a mobile wireless communication appliance **130** carried on or by the incarcerated individual and thus the beacon signal produced by the mobile transmitter **112** which is worn by the individual is indicative of the presence of the first monitoring unit. This physical relationship is exploited as described below. The processor circuit **115** of the first monitoring unit is in communication with a processor of the mobile wireless communication appliance which in turn is in communication with a wireless transceiver thereof so that the processor can communicate with the monitoring station and other devices, such as the signaling apparatus **101**. Thus, the wireless transceiver of the mobile wireless communication appliance itself may act as the transmitter **117** of the first monitoring unit **114**.

The second monitoring unit **116** may be part of a stationary communication appliance **132** and the processor circuit **121** and transmitter **123** thereof may be operable to communicate with the monitoring station **118** and other devices such as the signaling apparatus **101** by a landline or may include a transceiver (not shown) to facilitate communications with the monitoring station and other devices such as the signaling apparatus **101** by wireless methods.

-32-

The second monitoring unit **116** may be geographically located near a docking station **134** or may be part of a docking station operable to recharge the mobile wireless communication appliance, as will be described in further detail below.

5

Referring to Figures **3** and **4**, the signaling apparatus **101** includes a detector **120** operable to produce a proximity signal indicating proximity of the first monitoring unit **114** relative to the second monitoring unit **116** and includes first and second transmitters **122** and **124**. The first transmitter **122** is operable to cause the proximity signal to be communicated to the first monitoring unit (**114**) and the processor circuit **115** of the first monitoring unit is configured such that, when the proximity signal indicates the first monitoring unit is in proximity to the second monitoring unit **116** the first receiver **113** of the first monitoring unit is put into a low power mode in which signals are not received from the mobile transmitter **112**. In general, the entire first monitoring unit may be placed in a low power mode.

10

15

20

When the proximity signal indicates that the first monitoring unit **114** is not in proximity to the second monitoring unit **116** the first receiver **113** and more generally the entire first monitoring unit, is set into a receive mode so that signals from the mobile transmitter **112** are received and processed by the first monitoring unit.

25

30

The second transmitter **124** is operable to cause the proximity signal to be transmitted to the second monitoring unit **116** and the processor circuit **121** of the second monitoring unit is configured such that in response to the proximity signal, the second monitoring unit receives and processes signals from the mobile transmitter **112** when the proximity signal indicates the first monitoring unit **114** is in proximity to the second monitoring unit and ceases receiving signals from the mobile transmitter when the proximity signal indicates the first monitoring unit is not in proximity to the second monitoring unit. Ceasing

-33-

reception of signals at the second monitoring unit may involve setting the second receiver **119** into a non-receive mode.

5 The detector (**120**) is configured to cause the proximity signal to indicate the first monitoring unit **114** is in proximity to the second monitoring unit **116** when the first monitoring unit is coupled to a docking port of the docking station. Coupling to the docking port of the docking station **134** may involve receiving the mobile wireless communication appliance **130** in a receptacle **135** of the docking station, plugging the mobile wireless communication appliance **130** into a pigtail connector of the docking station, or engaging a wireless link such as a Bluetooth® link, or infrared link between the docking station and the mobile wireless communication appliance. Each of these components may act as a docking port to which the first monitoring unit may be coupled.

15 Referring to Figures **3** and **4**, the detector **120** is configured to produce a proximity signal to indicate the first monitoring unit **114** is not in proximity to the second monitoring unit **116** when the first monitoring unit is uncoupled from the docking station **134**. Thus, when the mobile wireless communication appliance **130** is away from the docking station **134** the detector **120** causes the proximity signal to indicate same and the first transmitter **122** transmits the proximity signal to the first monitoring unit **114** causing it to actively receive signals from the mobile transmitter **112** and the second transmitter **124** transmits the proximity signal to the second monitoring unit **116** causing the second monitoring unit **116** to ignore signals from the mobile transmitter. Thus, when the first monitoring unit **114** is not in proximity to the second monitoring unit **116** the first monitoring unit **114** transmits processed signals to the monitoring station **118** while the second monitoring unit **116** does not.

30 When the mobile wireless communication appliance **130** is in the docking station **134** the detector **120** produces the proximity signal to indicate same and the first transmitter **122** transmits the proximity signal to the first monitoring unit **114** causing it to enter the low power mode in which it does

-34-

not receive signals from the mobile transmitter **112** and the second transmitter **124** sends the proximity signal to the second monitoring unit **116** causing it to receive and process signals from the mobile transmitter **112**. Thus, when the first monitoring unit **114** is not in proximity with the second monitoring unit **116**, the second monitoring unit **116** transmits processed signals to the monitoring station **118** while the first monitoring unit **114** does not.

Detecting whether or not the mobile wireless communication appliance **130** is coupled to or uncoupled from the docking station **134** may be achieved using a docking station detector **136** employing the flag or battery current direction methods described above in connection with the embodiment shown in Figures **1** and **2**, for example, or other detection methods may be employed.

As an alternative to direct detection of whether or not the mobile wireless communication appliance **130** is coupled to or uncoupled from the docking station **134**, detecting proximity of first and second monitoring units **114** and **116** may be determined by measuring signal strength of the beacon signal received from the mobile transmitter **112**, since the mobile transmitter **112** and the first monitoring unit are carried by the same incarcerated individual. In this embodiment, the detector **120** comprises a signal strength detector **138** operable to detect signal strength of signals received from the mobile transmitter **112** and to produce the proximity signal in response to measured signal strength.

Many off-the-shelf radio frequency receivers have outputs representing a signal strength value of a signal received and demodulated from a radio frequency source, in addition to a signal output at which a demodulated version of the radio frequency signal is produced. Such a radio frequency receiver may act as the signal strength detector **138** to produce a signal representing signal strength. The signal strength detector **138** may further include a processor circuit **140** configured to determine whether or not the signal representing signal strength meets a first signal strength criterion. The

-35-

signal strength detector **138** causes the proximity signal to indicate the first monitoring unit **114** is in proximity to the second monitoring unit **116** when measured signal strength of the beacon signal from the mobile transmitter **112** meets the first signal strength criterion. The signal strength detector **138** may be configured to determine the first signal strength criterion is met when the measured signal strength is above a first signal strength threshold value.

Similarly, the signal strength detector **138** causes the proximity signal to indicate the first monitoring unit **114** is not in proximity to the second monitoring unit **116** when measured signal strength of the beacon signal meets a second signal strength criterion. The signal strength detector **138** may determine the second signal strength criterion is met when the measured signal strength is below a second signal strength threshold value. The first and second signal strength threshold values may be the same or different, or may differ over time depending on operating conditions. For example, the first and second signal strength threshold values may be set to values that create a hysteresis effect, whereby setting the proximity signal to indicate the first monitoring unit **114** is in proximity to the second monitoring unit **116** occurs at a different signal strength when measured signal strength of the beacon signal is increasing as compared to the measured signal strength of the beacon signal at which the proximity signal is set to indicate the first monitoring unit **114** is not in proximity to the second monitoring unit **116** when measured signal strength of the beacon signal is decreasing.

Thus, while the mobile wireless communication appliance **130** and hence the mobile transmitter **112** is sufficiently far away from the docking station **134** the signal strength detector **138** detects a relatively weak beacon signal or no signal from the mobile transmitter **112** and causes the proximity signal to indicate the first monitoring unit **114** is not in proximity to the second monitoring unit **116**. The first monitoring unit **114** thus receives and processes signals from the mobile transmitter and transmits these signals to the monitoring station **118**.

-36-

As the mobile wireless communication appliance **130** and hence the mobile transmitter **112** is brought nearer the signal strength detector **138**, the beacon signal strength measured by the detector increases. When the beacon signal strength meets the first criterion, the signal strength detector **138** causes the proximity signal to indicate the first monitoring unit **114** is in proximity to the second monitoring unit **116** and the first and second transmitters **122** and **124** transmit the proximity signal indicating this to the first and second monitoring units **114** and **116** respectively. In response, the first monitoring unit **114** enters its low power mode and the second monitoring unit **116** begins receiving and processing the signals received from the mobile transmitter **112** and transmits the processed signals to the monitoring station **118**. Thus, the second monitoring unit **116** "takes over" receiving and processing from the first monitoring unit **114** when the first monitoring unit is brought into proximity with the second monitoring unit.

As a further alternative to detecting the presence of the mobile wireless communication appliance in the docking station, and to measuring signal strength, the detector **120** may include a position signal receiver **144** operable to receive position signals representing a geographical position of the first monitoring unit (**114**), and the detector **120** produces the proximity signal in response to the position signals. The position signal receiver **144** may be of a type that comprises a global positioning system (GPS) signal receiver **146**, or a Long Range Radio Navigation (LORAN) receiver **148**, for example. Alternatively, the position signal receiver **144** may include a processor circuit **150**, which may communicate with an interface **152** to the wireless network or public switched telephone network. The position signal receiver **144** may further include a message receiver **154** operable to receive messages from a messaging system, the messages including data representing position signals specifying the geographical position of the first monitoring unit **114**. Effectively, a position signal produced by the wireless network by triangulation, may be formatted by the wireless network in a message

-37-

compatible with the SMS message format or the GPRS/CDMA 1X, CDPD, Mobitex, or 1XRTT data packet format, or any other suitable format, for example.

5 In an embodiment employing the position signal receiver **144**, regardless of how the position signals are received at the apparatus, the detector **120** is operable to cause the proximity signal to indicate the first monitoring unit **114** is in proximity to the reference position when the position signals meet a first position criterion. The detector **120** may be configured to determine the first
10 position criterion is met when the position signals indicate the first monitoring unit **114** is within a first range of the reference position. For example, the detector **120** may be configured to cause the proximity signal to indicate the apparatus **30** is in proximity to the reference position when the position signals indicate the apparatus is within **300** feet (**100m**) of the reference
15 position. The reference position may correspond to the geographical position of the second monitoring unit **116**.

Similarly, the detector **120** may be operable to cause the proximity signal to indicate the first monitoring unit **114** is not in proximity to the reference
20 position when the position signals meet a second position criterion and the detector may be configured to determine the second position criterion is met when the position signals indicate the first monitoring unit **114** is within a second range of the reference position. For example, the detector **120** may be configured to cause the proximity signal to indicate the first monitoring unit
25 is not in proximity to the reference position when the position signals indicate the first monitoring unit is more than **300** feet (**100m**) from the reference position.

Regardless of how the proximity signal is produced, in one embodiment, the
30 first transmitter **122** is operable to transmit a message representing the proximity signal to the first monitoring unit **114**. To facilitate this, in one embodiment, the first transmitter **122** includes a messaging service interface

-38-

5 **156** operable to transmit a message to the first monitoring unit **114** through a messaging service. The messaging service interface **156** may be operable to transmit a message compatible with the SMS message format or the GPRS/CDMA 1X, CDPD, Mobitex, or 1XRTT data packet format, or any other suitable format, for example.

10 Similarly, in one embodiment the second transmitter **124** may be operable to transmit a message representing the proximity signal to the second monitoring unit and the second transmitter may include a messaging service interface **158** operable to transmit a message to the second monitoring unit through a messaging service which may be the same or a different messaging service used by the first transmitter.

15 Referring to Figure 5, in one embodiment the signaling apparatus shown in Figure 4, and the monitoring unit **114** shown in Figure 3 may be housed in a common housing such as a modular battery unit **162** of the mobile wireless communication appliance **130**. In this embodiment, the modular battery unit **162** includes a battery **161** operable to supply power to the mobile wireless communication appliance **130** and includes a bus interface **164** in communication with a processor circuit **160** of the wireless communication appliance. The signaling apparatus **101** described above is partly implemented by a processor circuit **168** operable to implement the first and second transmitters **122** and **124** and includes the detector **120**. The detector **120** may include any or a combination of the docking station detector **136**, the signal strength detector **138** or the position signal receiver **144**. The processor circuit **168** may implement the processor circuit **115** of the first monitoring unit **114** and may be connected to the first receiver **113** which is also housed in the modular battery unit **162**. Simple modifications that would be apparent to those in the art may be made to a program controlling the wireless communication appliance processor circuit **160** to facilitate communication between the processor circuit **168** and the processor circuit **160** of the wireless communication appliance to permit a radio transceiver **163**

20

25

30

-39-

of the wireless communication appliance to be used to transmit signals produced by the processor circuit **168** to the monitoring station **118** in response to the beacon signal.

5 As will be appreciated the proximity signal may be produced by a variety of methods as described above. The proximity signal is transmitted directly to the first receiver **113** to directly control it to place it in the receive mode or the low power mode, depending on the state of the proximity signal. The processor circuit **168** acting in its capacity as the second transmitter **124**, also
10 transmits a message representing the proximity signal to the wireless communication appliance processor circuit **160** which causes the radio transceiver **163** to transmit the message via any suitable messaging format such as those described above to the second monitoring unit **116** shown in Figure 3. In response the receiver **119** of the second monitoring unit **116**, is
15 placed in a receive mode or a non-receive mode depending on the state of the proximity signal.

Referring to Figure 6, in another embodiment, the signaling apparatus **101** is housed in the docking station **134**, in addition to the second monitoring unit
20 **116**. The detector **120** of the signaling apparatus **101** is in communication with the processor circuit **121** and may include the docking station detector **136**, the signal strength detector **138** or the position signal receiver **144** described above. The processor circuit **121** itself may perform some of the functions of the detector **120** including determining whether criteria are met
25 and producing the proximity signal accordingly, as described above. The geographical position of the docking station **134** may be taken as the reference position in setting the criteria for setting the proximity signal active in response to the position signals, for example.

30 In addition the processor circuit **121** is configured to implement the first and second transmitters **122** and **124** whereby the first transmitter includes a message service interface **156** to facilitate transmitting a message via the

-40-

transmitter **123** to the first monitoring unit **114**, the message representing the proximity signal, for controlling the first receiver **113** of the first monitoring unit **114**. In addition, the processor circuit **121** is configured to directly control the second receiver **119** to transmit the proximity signal thereto to cause it to enter the receive mode or non-receive mode, as appropriate, in response to the proximity signal and thus acts as the second transmitter **124**. The message may be in any of the formats described above, for example.

When the proximity signal is set active to indicate the first monitoring unit **114** is in proximity to the second monitoring unit in response to whichever detector type is used, the processor circuit **121** sends a signal to the second receiver **119** causing it to enter its receive mode and causes a message to be sent to the first monitoring unit **114** using the transmitter **123**, to cause the first receiver **113** of the first monitoring unit **114** to enter the low power mode.

When the proximity signal is set inactive to indicate the first monitoring unit **114** is not in proximity to the second monitoring unit **116**, the processor circuit **121** sends a signal to the second receiver **119** causing it to enter its non-receive mode and causes a message to be sent to the first monitoring unit to place the first receiver **113** thereof into the receive mode. In this way the second receiver **119** in the docking station receives the beacon signal from the mobile transmitter **112** when the first monitoring unit **114** is in proximity to the second monitoring unit **116** and the first receiver **113** in the first monitoring unit receives the beacon signal from the mobile transmitter when the first monitoring unit is not in proximity to the second monitoring unit.

While specific embodiments of the invention have been described and illustrated, such embodiments should be considered illustrative of the invention only and not as limiting the invention as construed in accordance with the accompanying claims.